

DESCRIPTION

Bitumen Primer is a premium quality non toxic water based Bitumen primer designed for varied applications as primer coat.

USES

Bitumen Primer provides an effective primer coat prior to application of torch applied bituminous waterproofing membranes and oxidised bitumen. Bitumen Primer is resistant to alkalies & acids and can withstand prolonged oxidation.

FEATURES

- Economical
- Waterproof & Weatherproof
- Anti Corrosive
- Non Toxic
- Brush or Spray applied

APPLICATION INSTRUCTIONS

Bitumen Primer is applied straight from the container with standard brushes, squeegees or airless spray equipment at an average coverage rate of 2-4 sqm/per litre.

STORAGE & PACKAGING

Store under cover, out of direct sunlight and protect from extreme temperatures. Shelf life is upto 12 months when stored as above. Failure to comply with the recommended storage conditions may result in premature deterioration of the product.

Bitumen Primer is available in 20 and 200 ltrs. drums.

HEALTH AND SAFETY

As with all Bitumen products caution should always be exercised. Protective clothing such as gloves and goggles should be worn. Treat any splashes to the skin or eyes with fresh water immediately. Should any of the product be accidentally swallowed, do not induce vomiting. Call for medical assistance immediately. Ensure that the container is available for medical attendant to examine any relevant instructions and contents details.

TECHNICAL DATA

Flash Point	Non Flammable
Tack Free Time	6 Hours at 30°C
Colour	Brown / Black
Specific Gravity	1.0
Coverage	2-4 m ² / Kg.



This data is subject to change / modify time to time due to continuous improvement of the products. Test results are given as per the tests conducted in the lab. The test results may vary due to climatic conditions.

TROPICAL COATINGS INTERNATIONAL PVT. LTD.

Regd. Off. : Plot No. D-1, B-Block, Autonagar, Visakhapatnam - 530 012, Andhra Pradesh, INDIA.

Email : info@tropicalcoatings.in

Website : www.tropicalcoatings.in