

Trop coat™ - E J F

Expansion Joint Filler

An ISO 9001:2015 Certified Company



DESCRIPTION

The normal practice in runways, bridges, buildings and road constructions is to provide expansion joint & cutting between cutting slabs of reinforced concrete at designed intervals, and at intersections with other constructions. These joint fillers are then covered with sealing compounds.

EXPANSION JOINT FILLER

Conforming to IS : 1838 (Part 1) 1983 Consists of a fibre board, impregnated with bituminous material to make it durable and waterproof.

PURPOSE

- To permit free movement of the concrete slabs during expansion and contraction.
- To provide a waterproof seal.
- To resist entry of foreign matter into the Joint space.

PHYSICAL CHARACTERISTICS

- Consists of a soft fibre board impregnated with bituminous materials
- Compressible
- Possesses a high degree of recovery, once compression is relaxed
- Non extruding
- Available in thickness of 12 mm, 18 mm and 25 mm

PACKAGING

- Expansion Joint Filler is supplied as 4' x 4' or 4' x 2' sheets as per requirements.

This data is subject to change / modify time to time due to continuous improvement of the products. Test results are given as per the tests conducted in the lab. The test results may vary due to climatic conditions.

TROPICAL COATINGS INTERNATIONAL PVT. LTD.

Regd. Off. : Plot No. D-1, B-Block, Autonagar, Visakhapatnam - 530 012, Andhra Pradesh, INDIA.

Email : info@tropicalcoatings.in

Website : www.tropicalcoatings.in

Total Solutions For Waterproofing With Bituminous Membranes